



如何使用 System Manager 配置 Fpolicy

https://kb-cn.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/How_to_configure_Fpolicy_using_System_...

Updated: Thu, 16 Apr 2026 21:56:49 GMT

适用于

- ONTAP 9
- Fpolicy

说明

本文介绍如何使用 System Manager 配置 Fpolicy。

操作步骤

1. 通过访问 <https://<Cluster management IP>> 登录 System Manager。
2. 选择 **INSIGHTS**，然后单击 **Fix It** 按钮，在 **Native FPolicy isn't configured** 中。
3. 选择 **Disallowed extensions** 并输入扩展名信息。
4. 指定要启用 Fpolicy 的 SVM 名称和卷名称

注意：在指定 SVM 和卷之前，应在该 SVM 和卷上禁用 Fpolicy，否则将不会列出 SVM 或卷。

合作伙伴备注

partnerNotes_text

追加信息

单击修复按钮，在 **Native FPolicy 未配置**

ONTAP System Manager

Search actions, objects, and pages

DASHBOARD

INSIGHTS

STORAGE

NETWORK

EVENTS & JOBS

PROTECTION

HOSTS

CLUSTER

Anti-ransomware is disabled on one or more volumes. You'll not be notified if these volumes are threatened or under a potential ransomware attack.

Learn more about an anti-ransomware solution.

One or more storage VMs aren't configured for anti-ransomware protection. Potential ransomware attacks of volumes in these storage VMs might not be noticed.

Learn more about an anti-ransomware solution.

Apply best practices

Login banner isn't configured

Login banner messages aren't configured for either the cluster or the storage VM or for both. Login banner messages are displayed to the users who attempt to access the cluster or storage VM. These messages could be used to accept terms and conditions or to communicate administrative information.

Learn more about best practices for security.

Native FPolicy isn't configured


Native FPolicy isn't configured on one or more NAS storage VMs. Specify the file extensions that are allowed or disallowed to be written on the volumes of this cluster to help prevent attacks from ransomware with known file extensions.

Learn more about an anti-ransomware solution.

Dismiss **Fix It**

输入扩展名并指定 SVM 和卷。

Disallowed extensions

 The following list contains over 3000 vulnerable file extensions that have been used in past ransomware attacks. Some of these extensions might be used by legitimate files in your environment, and blocking them can lead to unexpected issues. Verify the list before configuring Native FPolicy.

MA, MB, MC, MD, ME, MF, MG, MH, MI, MJ, MK, ML, MM, MN, MO, MP, MQ, MR, MS, MT, MU, MV, MW, MX, MY, MZ, NA, NB, NC, ND, NE, NF, NG, NH, NI, NJ, NK, NL, NM, NN, NO, NP, NQ, NR, NS, NT, NU, NV, NW, NX, NY, NZ, OA, OB, OC, OD, OE, OF, OG, OH, OI, OJ, OK, OL, OM, ON, OO, OP, OQ, OR, OS, OT, OU, OV, OW, OX, OY, OZ, PA, PB, PC, PD, PE, PF, PG, PH, PI, PJ, PK, PL, PM, PN, PO, PP, PQ, PR, PS, PT, PU, PV, PW, PX, PY, PZ, QA, QB, QC, QD, QE, QF, QG, QH, QI, QJ, QK, QL, QM, QN, QO, QP, QQ, QR, QS, QT, QU, QV, QW, QX, QY, QZ, RA, RB, RC, RD, RE, RF, RG, RH, RI, RJ, RK, RL, RM, RN, RO, RP, RQ, RR, RS, RT, RU, RV, RW,

Allowed extensions

^ View all storage VMs

<input checked="" type="checkbox"/> Storage VM
<input type="checkbox"/> cifsmartin
<input type="checkbox"/> svm2_ontap914
<input checked="" type="checkbox"/> svm4_ontap914
<input type="checkbox"/> svmtest_914

^ View volumes for selected storage VMs

Unselect the volumes to exclude them from Native FPolicy

<input checked="" type="checkbox"/> Volume	Storage VM
<input checked="" type="checkbox"/> vol1_svm4	svm4_ontap914
<input type="checkbox"/> svm4_ontap914_root	svm4_ontap914

I have verified the list of either allowed or disallowed extensions.

Configure

Cancel

内部参考

一般来说，通过 System Manager 修改 file-extensions-to-include 的工作流程是首选方法。

如果客户需要一种以脚本方式进行此类修改的方法，则下面 URL 中的脚本可能会有所帮助，但测试不够彻底。因此，应谨慎使用，并应在使用前验证由此产生的 file-extensions-to-include。

[1]

1. [How to configure Fpolicy using System Manager#Applies_to](#)
2. [How to configure Fpolicy using System Manager#Description](#)
3. [How to configure Fpolicy using System Manager#Procedure](#)
4. [How to configure Fpolicy using System Manager#Partner_Notes](#)
5. [How to configure Fpolicy using System Manager#Additional_Information](#)
6. [How to configure Fpolicy using System Manager#Internal_Notes](#)