

NiCE

ONTAP 升级后加权路由指标已更改

https://kb-cn.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/Weighted_route_metric_changed_after_ON…
Updated: Tue, 24 Nov 2026 04:55:11 GMT

适用于

ONTAP 9

问题

- 首选默认路由在 ONTAP 升级后从一个 VLAN（加权度量为 10）更改为另一个 VLAN（加权度量值从 12 修改为 5）
- 最低度量优先。

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information contained herein may be used solely in connection with the NetApp products discussed in this document.'

升级前

节点	SVM	目标	子网组	接口	网关	指标	标记	引用计数	查找计数	路径 MTU	路由地址
nodeA	vserver1	0.0.0.0/0	默认	a25b-3007	10.0.0.1	12	UGS	5	81470953	9000	10.
nodeA	vserver1	0.0.0.0/0	默认	a25c-1007	10.10.0.21	10	UGS	0	2124167	9000	10.

升级后

节点	SVM	目标	子网组	接口	网关	指标	标记	引用计数	查找计数	路径 MTU	路由接口地址
nodeA	vserver1	0.0.0.0/0	默认	a25b-3007	10.0.0.1	5	UGS	6	1021	9000	10.0.0.
nodeA	vserver1	0.0.0.0/0	默认	a25c-1007	10.10.0.21	10	UGS	0	12	9000	10.0.0.

© 2023 NetApp.No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner. For more information, see Legal Notices.