



## LDAP 错误：需要强身份验证：处理签名和密封要求CIFS 设置、用户映射和其他操作失败

[https://kb-cn.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/LDAP\\_Error\\_\\_Strong\\_authentication\\_is\\_req...](https://kb-cn.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/LDAP_Error__Strong_authentication_is_req...)

Updated: Fri, 17 Apr 2026 03:26:33 GMT

### 适用于

ONTAP 9

### 问题

- 由于 LDAP 客户端安全要求，创建 CIFS 服务器、某些用户映射操作和其他依赖 LDAP 的调用失败

- 这些错误的示例：
  - LDAP 错误：Strong authentication is required
  - 错误：Strong(er) authentication required
- 以下是由于 LDAP 客户端安全要求而导致的"cifs setup"失败的示例：

```
Error: Failed to create CIFS server. Reason: Failed to create the Active
Directory machine account
"VSERVERNAME". Reason: LDAP Error: Strong authentication is required.
Error: Machine account creation procedure failed
[ 0 ms] Trying to create machine account 'VSERVERNAME' in domain
'DOMAINAME' for virtual server 'VSERVERNAME'
[ 30] Found XX domain controllers through DNS
[ 35] Connecting to LDAP (Active Directory) server XXXX (X.X.X.X) as
name@domain.com
**[ 36] FAILURE: 'CifsServer' configuration not available
[ 82] Unable to connect to XXXX through the X.X.X.X interface (Error:
Strong(er) authentication required)
[ 84] Connecting to LDAP (Active Directory) server XXXX (X.X.X.X) as
name@domain.com
[ 123] Unable to connect to XXXX through the X.X.X.X interface (Error:
Strong(er) authentication required)
[ 126] Connecting to LDAP (Active Directory) server XXXX (X.X.X.X) as
name@domain.com
[ 164] Unable to connect to XXXX through the X.X.X.X interface (Error:
Strong(er) authentication required)
```